



Shinmizu Pte Ltd

Co. Reg No: 201628804M

WATER DISPENSER SD1050 SERIES

FEATURES

- ECO Mode System: Automatically power off the heating system at night by photo detector.
- Hygiene Guard: Protects the faucet from bacterial growth. Replaceable during service.
- Hot Water Safety Device: Safety device can protect your children from unexpected hot water accidents.
- Colour Code Taps: Replaceable colour panel can be interchanged with various colours.



SD1050SP

Model	SD1050SP	SD1050
DIMENSIONS	300mm (W) 340mm (D) 552mm (H)	300mm (W) 340mm (D) 1025mm (H)
WEIGHT	17kg	21kg
COMPRESSOR	1/11 HP Sealed Type	
MOTOR POWER CONSUMPTION	90~120W	
REFRIGERANT	R-134a	
COLD WATER TANK	304 Stainless Steel 3L Tank	
COLD WATER CAPACITY	20 cups at 4~12°C	
TEMP. CONTROL OF COLD WATER	By Thermostat (in cold)	
COOLING	Forced Cooling Type	
HEATER POWER CONSUMPTION	480W	430W
HOT WATER TANK	304 Stainless Steel 1.7L Tank	
HOT WATER CAPACITY	10 cups at 75~90°C	
HEATER	Band Heater	
TEMP. CONTROL OF HOT WATER	By Bi-metal (automatic return)	
OVERHEAT PROTECTION DEVICE	By Bi-metal (automatic return)	
REGULATED POWER	AC 220~240V / 50~60Hz	
FRONT PANEL	ABS	
SIDE PANEL	EGI	
FAUCET	ABS Assembly	
PURIFICATION SYSTEM	None	UF Type



SD1050